



ISSN: 2350-0328

**International Journal of Advanced Research in Science,
Engineering and Technology**

Vol. 7, Issue 2 , February 2020

Improvement of Irrigated Lands the Research Results of Fixing Disc Device in Base Land Straightener Scoop

Kuchkarov Jurat Jalilovich , Sattorov Shaxzod Yarashovich , Muzaffarov Rajab

External doctorate student, Bukhara branch of the Tashkent Institute of Irrigation and Agricultural Mechanization Engineers, the Republic of Uzbekistan

Bukhara branch of the Tashkent Institute of Irrigation and Agricultural Mechanization Engineers, the Republic of Uzbekistan

External doctorate student, Bukhara branch of the Tashkent Institute of Irrigation and Agricultural Mechanization Engineers, the Republic of Uzbekistan

ABSTRACT: The article presents the results of laboratory experiments to determine the productivity and some other parameters of the disk working body, working with the scheduler bucket in order to improve the process of leveling fields that meet the agro technical requirements of pre-sowing background.

KEY WORDS: productivity, disk, bucket filling coefficient, disk diameter, drawing prism. water saving, furrow irrigation, disk space, innovative technologies, the mechanic, long-base scheduler.

I. INTRODUCTION

The Resolution of the Cabinet of Ministers of the Republic of Uzbekistan dated February 24 , 2014 No. 39 “On additional measures to ensure the unconditional implementation of the State Program for the improvement of the ameliorative state of irrigated land and rational use of water resources for 2013-2017” was adopted [1]. Taking into account these land reclamation, land leveling the level of effective demand and use. One of the technologies used to enforce this solution, i.e. crop irrigation, efficient use of water resources, is a smooth surface. It can be concluded that the area of machine-tractor units is even, if the landing area is above the plane of the surface.

This is article based on importance of something the land and done it in the given time according to agro techniques demands the number of grader in something irrigated lands of Bukhara province is also based on given formulas. There are also given advice in using efficiently something aggregates. Something irrigated land makes condition of increasing fruit fellness of agriculture crops , not much work during irrigating the land and saving water, polishing quality row spaces and gathering crop quality with machines. Polishing soil several time mike land uneven when irrigate the land , in other word while tilling long furrow and after irrigating high – lowland and last year uneven will be formed. There are also observed some part of the field after irrigating sever al time. It may also achieved in good or quality something by long grader machines two or three times but it can’t be smoothed by hanging grader machines. Smoothing the land in agro techniques time ameliorate the land.

Smoothing aggregate should be provided enough for usefully and smoothed the land in agro technique time on conclusion of several scientist general smoothing land consist of 35 .. 40% in our republic According to the observation in Vobkent , and G’ijduvon , region of Bukhara irrigating furrow cotton land in not smoothing fields moisture consists of in deep part of the land 8.....12% in high part 10...15% that’s why we can’t achieve moisture in all part of crop it increased salt. This make a result of decreasing crop [3].

II. PROPOSED METHODOLOGY

Accurate and reliable aggregate performance will improve their business efficiency and quality of work. In order to increase the leveling efficiency of the land based on its underwire buckets, spherical disks are installed in order to analyze optimal size models and laboratory experiments. We have developed disk drives of the following diameters:

150 mm, 120 mm, for experiments in a soil channel with a workstation from a recycled disk. The experiments were performed in triplicate and at three speeds (0.25 m / s, 0.58 m / s, 0.80 m / s).

We have developed disk drives of the following diameters: 150 mm, 120 mm, for experiments in a soil channel with a workstation from a recycled disk. The experiments were performed in triplicate and at three speeds (0.25 m / s, 0.58 m / s, 0.80 m / s). In order to identify the optimal variant of the disk disassembly scheme, vertical and horizontal slots (grooves) were made on the sides of the pile. According to the results of the experiment, the dependence of the soft disk device model on the diameter and speed of the disk was investigated. Laboratory studies also show that increasing the layout increases with increasing diameter, distance and speed of the disks in the model. Studies have shown that the process of forming a ground coating on a dirt channel occurs several times slower than in field conditions. There was no destruction of the disk between the disks by increasing the speed of movement of the base device to the base station of the ground channel by 0.80 m / s, on the contrary, the level of crushing increased. In addition, if the height of the ground cellar exceeds 5 cm, the smooth movement of the hard disk to the ground leveling plane will deteriorate. At the same time, part of the soil inside the puddle falls from the side and rear walls, which reduces the quality of the drift plane in the soil channel. Analysis of the research results showed that several effective disk characteristics were found with a diameter of $D_d = 150$ mm.

Laboratory results also show that the efficient operation of model workstations of a disk device, which softens the base plate, is associated with the optimum displacement of disks. We changed the disk space by tilting it. Optimized disks in disks are the displacement of disks with soil, minimization of the walls of the side and rear sides, as well as the smooth displacement of the soil in the heap. studying the soil coagulation process based on the speed of the drive model and analyzing photos taken with a fast merging photo demonstrated that the discriminating organization works more efficiently ... When the distance is 20%, the distance between the disks should be $L \leq (2 \dots 3) D_d$

The angle of inclination of the disk space is of great importance for the horizontal plane. This is due to the fact that the inclination of the disk on which the disk was rolled should be flattened and crushed. According to the literature, the natural angle of soil inclination [4] should be from 40 to 50, based on the physical and mechanical properties of the soil. However, observations have shown that the length of the slope of mountaineering in motion is less than the length of the slope of the stop line. Thus, the slope of the leveling of the soil is much greater than when driving. Given the above analysis, we assume that the slope of the motion of the soil is 55.... 65 .

III. RESULT ANALYSIS

The corner of the slope depends on the physical and mechanical properties of the soil and the moisture content. This corresponds to the results of experiments conducted on the soil channel. As can be seen, the inclination of the disk surface should correspond to the straight line of the soil coil and should be not less than 50 ... 100 mm below the center of the soil. These indicators depend on the speed and humidity of the pile (speed $y = 0.25 \dots 0.80$ m / s, humidity $W = 14 \dots 20\%$). If this speed and humidity exceed working quality, the soil will not even soften between the discs. Soil moisture, its hardness, weight and composition of soil aggregate were determined by three layers at a depth of 10 cm before and after crossing the groundwater channel of the disk device, which softens to the ground plane. The following tables show the measurement results . (Tables 1, 2 ,3)

Picture-1.

A mockup of a data table model that simplifies alignment on land.



The change in the hardness of the soil depending on the speed of movement of the working body on the disk of the device softens to the base of the plateau.

Table-1

Horizons,sm	Soil moisture, percentage calculation	hardness of the soil, kg / cm ²			
		Until the passage of aggregate	Speed moving of aggregate after the passing m/s.		
			0.25	0.58	0.80
Getting cut the height of soil					
0...5	16,48	3,35	6,40	6,42	6,0
5...10	17,62	5,05	8,30	8,50	6,3
Feeling the depth					
0...5	16,48	3,5	3,0	2,5	3,2
5...10	17,62	5,6	4,5	3,3	3,9

Depending on the velocity of the moving body of the working body, the disk device that softens the base plate to change the weight of the soil.

Table -2

Horizons,sm	The weight of the soil, g / cm ³			
	Until the passage of aggregate	Speed moving of aggregate after the passing m/s.		
		0.25	0.58	0.80
0...5	1,41	1,42	1,41	1,40
5...10	1,43	1,43	1,42	1,41

The change of the composition of the soil aggregate, depending on the speed of movement of the working organ on the disk device softening to the base plateau.

Table-3

Movement speed, m / s	Amount of Fractions,%		
	∅ 10...5mm	∅ 5... 0,25mm	∅ < 0,25mm
Untill the passing of aggregate			
	59,1	28,89	11,19
After the passing og aggregate			
0,25	57,8	29,72	12,06
0,58	56,91	33,26	9,72
0,80	54,23	36,67	8,71

Change of leveling profile of the longitudinal profile, depending on the velocity of movement of the working body by the disk device softening to the base plateau.

Table-4

Tendency Indicator	Movement speed, m / s		
	0,25	0,58	0,80
σ_{θ}	9,91	11,05	10,80
σ_{π}	8,6	9,37	9,02
K (%)	13,21	15,2	16,48



ISSN: 2350-0328

International Journal of Advanced Research in Science, Engineering and Technology

Vol. 7, Issue 2, February 2020

IV. CONCLUSION

As can be seen from the table, soil hardness, volume and aggregate content will vary at a rate of 0.25 ... 0.80 m / s and a relatively small amount of moisture content. This change corresponds to the agrotechnical requirements before planting. Table 4 shows that aggregate velocity increased from 0.25 m / s to 0.80 m / s, whereas the level of longitudinal profile of the ground canal increased by 19.84%. This change confirms the theoretical results. A smooth disc leveling device based on the slope, the slope of the soil heap from the soil surface should be parallel to the line and the middle of the pile should be placed at least 50 ... 100 mm. These indicators depend on the speed and humidity of the pile (speed $y = 0.25 \dots 0.80$ m / s, humidity $W = 14 \dots 20\%$). This speed is reduced, and the humidity improves the quality of work, and the soil is blocked on the surface of the disks.

REFERENCES

1. Resolution of the Cabinet of Ministers of the Republic of Uzbekistan dated February 24, 2014 No. 39 "On additional measures to ensure the unconditional implementation of the State Program for the improvement of the ameliorative condition of irrigated land and the rational use of water resources for 2013-2017".
2. P.G Hikmatov and others. Theoretical prerequisites for determining the productivity of the shneck, working with the scheduler bucket. Russia. "Agrarian science" scientific-theoretical and industrial journal. №6.2015
3. Khasanov I.S. and others. Determination of the productivity of a screw working body. Russia. "Agrarian science" scientific-theoretical and industrial journal. № 6.2016
4. Akhmedzhanov M.A. "Planning of irrigated land". "Mekhnat", Tashkent, 1991.
5. The Decree of the President of the Republic of Uzbekistan № PP-3405 "On the State Program of Irrigation and improvement of ameliorative condition of irrigated lands for 2018-2019". Tashkent, 27 November 2017.
6. Berdyansky V.N, Atajanov A.U, Method of extraction. Initial Patent No. 1114. July 30, 1997. July. No. 4.
7. Copyright certificate of the Republic of Uzbekistan No. IH DP 9600689.1. (19) UZ (11) 4619 B. (51) 6A 01 G 25/00 1996
8. Cultivator-plant feeding cotton universal KHU-4. M. GOSNITI 1988
9. T.M.Bashta. Volumetric pumps and hydraulic motors of hydraulic systems. M., Mechanical Engineering, 1974. Page 496-497.
10. Atadjanov A.U. Improving the technology of planning the irrigated field along the furrows. Collection of scientific papers. Tom. 46. series 3.1. 69-71 pp. Ruse. Bulgaria. 2007
11. Atadjanov A.U. Irmukhamedova L.Kh., Atadjanov A.A. The technology of planning the irrigated field, providing uniform soil moisture. International scientific journal "Young Scientist". G.Kazan. No. 8 (142) /2017 pp. 43-46
12. Atadjanov A.U., Matyakubov B.Sh. Improving the technology to ensure uniform wetting of the root layer of soil irrigated by furrows. International scientific-practical conference "Water for the sustainable development of Central Asia." March 23-24, 2018 Dushanbe, Tajikistan. Page 237-241
13. Atadjanov A.U. Technology of preparation of lands for furrow irrigation. Scientific application of the journal "Agro science", "Agriculture of Uzbekistan". Tashkent. Issue 4 2007. 25 pages.